

# COMPACT LED



## OFFICE LIGHTING



### CHARACTERISTIC

Supply voltage:	230V
Frequency:	50Hz
Ingress protection IP:	IP44/IP20
Rated power:	32W, 50W
Energy efficiency class:	EEI=A
Electrical protection class:	II
Dimensions:	595/595/66mm
Net weight of 1 unit:	1,9kg
Material of the body:	ABS
Colour temperature:	3000K, 4000K
Mounting version:	Recessed
Colour of the body:	White
Luminous flux* :	max. 5700lm
Material of the diffuser:	PMMA
Type of the diffuser:	Opal / PRM
Light source:	LED GO!

\* Initial, tolerance +/- 10%

### SPECIFICATION

Compact LED luminaire designed for installation in modular ceilings. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

### APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.

# COMPACT LED

## OFFICE LIGHTING

### AVAILABLE OPTIONS

[Click on index to go to detailed catalogue extract](#)

Index	Rated power	Colour temperature	Luminous flux **	Material of the diffuser	Type of the diffuser	Energy efficiency class
» 904004	32W	3000K	3350lm	PMMA	Opal	A +
» 904011	32W	4000K	3600lm	PMMA	Opal	A +
» 904066	36W	3000K	3650lm	PMMA	Opal	A +
» 904073	36W	4000K	3950lm	PMMA	Opal	A +
» 904028	32W	3000K	3650lm	PMMA	PRM	A +
» 904035	32W	4000K	3950lm	PMMA	PRM	A +
» 904042	36W	3000K	3950lm	PMMA	PRM	A +
» 904059	36W	4000K	4300lm	PMMA	PRM	A +
» 904103	50W	3000K	4850lm	PMMA	Opal	A +
» 904110	50W	4000K	5300lm	PMMA	Opal	A +
» 904080	50W	3000K	5250lm	PMMA	PRM	A +
» 904097	50W	4000K	5700lm	PMMA	PRM	A +

\*\* Initial, tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product.  
Product data sheet does not constitute an offer.

Revision date: 2016-04-20



Lena Lighting S.A.  
ul. Kornicka 52  
63-000 Sroda Wielkopolska

tel. +48 (61) 28 60 300  
fax.+48 (61) 28 54 059  
e-mail: office@lenalighting.pl  
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE.



This product is a subject to electric and electronic waste equipment regulations (WEEE).



2/2016